K-CDF Compact 13mm Partition System Specification

5214 KERMAC PARTITION SYSTEM

1. **GENERAL**

This section relates to the supply and installation of **KerMac Industries** partitioning systems using proprietary, prefabricated toilet partitions and screens. It includes;

- K-CDF Compact 13mm Partition System

1.1 **RELATED WORK**

Refer to ~ for ~

Documents

1.2 **DOCUMENTS**

Refer to the general section 1233 REFERENCED DOCUMENTS. The following documents are specifically referred to in this section:

NZBC C/AS1-AS7 Protection from fire

JIS Z 2801 Antibacterial products - Test for antibacterial activity and efficacy

MANUFACTURER/SUPPLIER DOCUMENTS 1.3

K-CDF Compact 13mm partition system brochure

Manufacturer/supplier contact details Company: KerMac Industries Web: www.kermac.co.nz Email: kerry@kermac.co.nz

09 273 1524 Telephone:

Warranties

WARRANTY - MANUFACTURER/SUPPLIER 1.4

Provide a material manufacturer/supplier warranty:

For panel integrity 5 years

Hardware 2 years

- Provide this warranty on the manufacturer/supplier standard form.
- Commence the warranty from the date of practical completion of the contract works.

Refer to the general section 1237 WARRANTIES for additional requirements.

1.5 WARRANTY - INSTALLER/APPLICATOR

Provide an installer/applicator warranty: 2 years For installation

- Provide this warranty on the installer/applicator standard form.
- Commence the warranty from the date of practical completion of the contract works.

Refer to the general section 1237 WARRANTIES for additional requirements.

Requirements

1.6 QUALIFICATIONS

Installers to be experienced, competent trades people familiar with the materials and techniques specified.

1.7 NO SUBSTITUTIONS

Substitutions are not permitted to any of the specified **KerMac Industries** systems, components and associated products listed in this section.

1.8 SAMPLES

Submit on request samples of panels and componentry for approval of colour and finishes.

Performance

1.9 SURFACE FIRE PROPERTIES

Group Number to NZBC C/AS2-AS7, table 4.1. Refer to SELECTIONS.

2. PRODUCTS

Materials – K-CDF Compact 13mm partition system

2.1 CHANNELS, RAILS AND BRACKETS

Extruded aluminium alloy 6060 with exposed face anodic coated

2.2 PANELS - COMPACT LAMINATE

Machine finished 13mm Swiss CDF panels with black core. Edges polished finish only. Certified antimicrobial to JIS Z 2801 to prevent the growth of bacteria on the surface up to 99% within 24 hours.

2.3 DOORS

To match the panels and predrilled for hardware. Doors to be flush with fascia panels. Door gaps not to exceed 2mm on installation.

Components

2.4 PEDESTALS

175mm adjustable cast pedestals with top and bottom to screw fix to panel and floor

2.5 HINGES

To match the aluminium section in size, two cast spring-loaded hinges per door with bolt through security fixings.

2.6 INDICATOR BOLT AND KEEPER

KerMac standard cast padel shift indicator bolt and keeper, polished finish.

2.7 HAT AND COAT HOOKS

KerMac standard cast coat hook with integrated door stop.

3. EXECUTION

Conditions

3.1 DELIVERY, STORAGE AND HANDLING

Take delivery, handle and store tracks, studs, panels and accessories on site on a level floor and cover.

Protect finished surfaces, edges and corners from damage.

Move/handle goods in accordance with manufacturer's requirements.

Reject and replace goods that are damaged or will not provide the required finish.

3.2 PRE-INSTALLATION REQUIREMENTS

Check work previously carried out and confirm it is of the required standard for this part of the work. Ensure substrate plumb, level and in true alignment.

Application

3.3 INSTALL SCREENS

Carry out the fixing, erection and fitting to finish rigid, plumb, true to line and face and square, to the KerMac Industries requirements.

3.4 INSTALL COMPONENTS

Hang doors and fit hardware to the KerMac Industries requirements.

Completion

3.5 ROUTINE CLEANING

Carry out routine trade cleaning of this part of the work including periodic removal of all debris, unused and temporary materials and elements from the site.

3.6 DEFECTIVE OR DAMAGED WORK

Repair damaged or marked elements. Replace damaged or marked elements where repair is not possible or will not be acceptable. Leave work with parts fully and freely working to the standard required for following procedures.

4. SELECTIONS

For further details on selections go to www.kermac.co.nz
Substitutions are not permitted to the following, unless stated otherwise.

Performance

4.1 SURFACE FIRE PROPERTIES

Group Number	Panel/Finish	Location
~	Compact Laminate	~

Materials - partition system

K-CDF COMPACT 13MM TOILET PARTITION SYSTEM

4.2

Brand:	KerMac Industries
System type:	K-CDF Compact 13mm Toilet Partition System
Panel description:	13mm Swiss CDF Compact Laminate panel
Panel colour:	~
Component colour	Channels/Rails/Brackets, Natural Silver anodised
Pedestal Height	175mm cast pedestals
Hardware	Cast polished finish